cavagna group
Wherever gas is used, we are there

c UL US LISTED

Two-stage Regulator Kit

Type 524AS - Vertical Vent





Picture shown in Clamshell

Technical Specifications

Inlets: 1/4" FNPT
Outlet: 3/8" FNPT
Capacity: 160,000 BTU/hr
Vertical Vent
Kit includes the plastic vent covers required by RVIA
For use on RVs with single vertical tank or horizontal tank

Safety Features

Overpressure Protection Device: Limits environmental propane release in case of regulator malfunction to a value less than 2 psi, significantly lower than that mandated by UL standard 144

Product Description

A combination regulator; first stage reduces cylinder outlet pressure to 10 psi, and then second stage maintains a stable working pressure of 11" water column.

Item Packaging

Code	Description	Type of Packaging	Carton Count
52-A-490-0018	Vertical Vent Regulator Kit Includes vent covers	Box	12
52-A-490-0019		Clamshell	

Type 524AS - Horizontal Vent



Technical Specifications

Inlets: 1/4" FNPT
Outlet: 3/8" FNPT
Capacity: 160,000 BTU/hr
Horizontal Vent
For use on RVs with single vertical tank or horizontal tank

Safety Features

Overpressure Protection Device: Limits environmental propane release in case of regulator malfunction to a value less than 2 psi, significantly lower than that mandated by UL standard 144

Product Description

A combination regulator; first stage reduces cylinder outlet pressure to 10 psi, and then second stage maintains a stable working pressure of 11" water column.

Item Packaging

Code	Description	Type Of Packging	Carton Count
52-A-490-0020	Two Stage Regulator Kit Includes vent covers	Box	12